

Please type a plus sign (+) inside this box →

+

PTO/SB/05 (4/98)

Approved for use through 09/03/00. OMB 0651-0032

Patent and Trademark Office: U. S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 16356.543 (DC-02404)

First Named Inventor or Application Identifier

Michael A. Brundridge

Express Mail Label No. EL 455943566 US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Commissioner for Patents

Box Patent Application

Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 20]
(preferred arrangement set forth below)
- Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure

6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

3. ☒ Drawing(s) (35 USC 113) [Total Sheets 12]
4. Oath or Declaration [Total Pages 2]
- a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuations/divisional with Box 17 completed)
 - [Note Box 5 below]
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting Inventor(s) named in the prior application, see 37 CFR 1.63(d) and 1.33 (b).

ACCOMPANYING APPLICATION PARTS


8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure ☒ Copies of IDS
Statement (IDS)/PTO-1449 Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEM 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign Priority is claimed)
16. ☒ Other: Express Mail Certificate

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____, filed: _____ prior application information. Examiner _____ Group/Art Unit _____

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label



or ☒ Correspondence address below

NAME	David L. McCombs				
	Haynes and Boone, LLP				
ADDRESS	901 Main Street				
	Suite 3100				
CITY	Dallas	STATE	TX	ZIP CODE	75202
COUNTRY	USA	TELEPHONE	214-651-5533	FAX	214-651-5940
Name (print/type)	James R. Bell			Registration No. (Attorney/Agent)	26,528
Signature				Date	8-7-00

a-101368.1

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of Time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

PATENT
Docket Number: 16356.543 (DC-02404)



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Michael A. Brundridge et al. §
Serial No. N/A § Examiner: N/A §
Filed: Herewith § Group Art Unit: N/A §
For: A System And Method For Identifying §
Executable Diagnostic Routines Using §
Machine Information And Diagnostic §
Information In A Computer System §

Box Patent Application
Commissioner for Patents
Washington, D.C. 20231

EXPRESS MAIL CERTIFICATE

Express Mail Number: EL 455 943566 US
Date of Deposit: AUGUST 7, 2000

I hereby certify that the following attached papers and fee:

1. Utility Patent Application Transmittal Sheet;
2. Fee Transmittal Sheet (in duplicate);
3. Patent Application consisting of 14 pages of Specification, 5 pages of Claims and 1 page Abstract of Disclosure;
4. 12 Drawing sheets;
5. Declaration and Power of Attorney;
6. Assignment and Recordation Cover Sheet;
7. Information Disclosure Statement with cited references;
8. Check in the amount of \$730.00 (\$690.00 for filing fee and \$40.00 for recordation of Assignment); and
9. A Return Postcard

are being deposited with United States Postal Service "Express Mail Post Office to Addressee" to the Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

PETRA RODRIGUEZ
Typed or Printed Name
Petra Rodriguez
Signature
A-101366.1

EXPRESS MAIL NO.: 92 455 943 566 US DATE OF DEPOSIT: AUGUST 7, 2000

This paper and fee are being deposited with the U.S. Postal Service Express Mail Post Office to Addressee service under 37 CFR §1.10 on the date indicated above and is addressed to: Box PATENT APPLICATION, Commissioner for Patents, Washington, D.C. 20231

Petra Rodriguez Petra Rodriguez
Name of person mailing paper and fee Signature of person mailing paper and fee

**A SYSTEM AND METHOD FOR IDENTIFYING EXECUTABLE
DIAGNOSTIC ROUTINES USING MACHINE INFORMATION
AND DIAGNOSTIC INFORMATION IN A COMPUTER SYSTEM**

Inventors: Michael A. Brundridge
428 Doe Run
Georgetown, TX 78628

Javier L. Jimenez
8926 Joachim Lane
Austin, TX 78717

Assignee: DELL PRODUCTS L.P.
One Dell Way
Round Rock, TX 78682-2244

David L. McCombs
HAYNES AND BOONE, L.L.P.
901 Main Street, Suite 3100
Dallas, Texas 75202
214/651-5533

002020"03422360

PATENT

Docket No.: DC-02404 (16356.543)

EXPRESS MAIL NO.: EL 455943566 US DATE OF DEPOSIT: AUGUST 7, 2000

This paper and fee are being deposited with the U.S. Postal Service Express Mail Post Office to Addressee service under 37 CFR §1.10 on the date indicated above and is addressed to: Box PATENT APPLICATION, Commissioner for Patents, Washington, D.C. 20231

PETRA RODRIGUEZ Ruth Rodz
Name of person mailing paper and fee Signature of person mailing paper and fee

**A SYSTEM AND METHOD FOR IDENTIFYING EXECUTABLE
DIAGNOSTIC ROUTINES USING MACHINE INFORMATION
AND DIAGNOSTIC INFORMATION IN A COMPUTER SYSTEM**

Background

The disclosures herein relate generally to computer systems, and more particularly, to a system and method for identifying executable diagnostic routines using machine information and diagnostic information in a computer system.

A computer system may include a diagnostic package with a set of diagnostic routines that may be executed to test components in the system. The manufacturer of the computer system may purchase a diagnostic package that includes a set of diagnostic routines from a third party vendor. The diagnostic package, however, may not include platform or operating system specific information that may be used to identify the diagnostic routines that are executable on a given platform and / or operating system.

A computer manufacturer may wish to support only certain devices on certain platforms and / or operating systems. For example, a computer manufacturer may wish to sell a computer system that does not support joysticks. The diagnostic package installed by the computer manufacturer in this computer system, however, may include a diagnostic routine for a joystick that is executable by a customer. Diagnostic packages typically do not include a method for restricting the display and execution of a diagnostic routine for a component which a computer manufacturer does not wish to support. Thus, in the example above, the computer manufacturer

may not be able to prevent the diagnostic routine for the joystick from being displayed and executed using only the diagnostic package.

It may be possible to write a custom installation program for each platform that specified only the components supported by each platform to allow only supported diagnostic routines to be displayed and executed. To do so, however, a computer manufacturer would need to write such a program for each different platform it offered. Such a program would require a costly and inefficient development effort and testing process for each platform sold by a manufacturer. A system and method is needed that identifies supported diagnostic routines in a diagnostic package for a given computer system regardless of the platform or operating system used by the computer system. A system and method is also needed to display only the supported diagnostic routines of the computer system to its user.

Summary

One embodiment, accordingly, provides a system and method for identifying executable diagnostic routines using machine information and diagnostic information in a computer system. To this end, a method includes detecting machine information and detecting diagnostic information corresponding to the machine information. The method also includes causing one of a plurality of diagnostic routines to be selectable for execution according to the diagnostic information.

A principal advantage of this embodiment is that an entire suite of diagnostic routines may be installed on each computer system offered by a computer manufacturer while only supported diagnostic routines may be made selectable for execution on a particular system based on certain characteristics of that system. In this way, the process of installing diagnostic routines may be substantially similar or even identical for each system that a computer manufacturer offers. In addition, this embodiment may advantageously allow a computer manufacturer to change the set of supported diagnostic routines on a system or systems while minimizing the development effort and test cycle for each change. The embodiment may also

advantageously allow a computer manufacturer to easily offer additional systems or test support with minimal development effort and testing.

Brief Description of the Drawing Figures

Fig. 1 is a diagram illustrating an embodiment of a computer system.

Fig. 2a is a flowchart illustrating a first part of an embodiment of a method for indicating available diagnostic routines using system information in a computer system.

Fig. 2b is a flowchart illustrating a second part of an embodiment of a method for indicating available diagnostic routines using system information in a computer system.

Fig. 3a is a diagram illustrating an embodiment of computer systems configured to communicate using a communications network.

Fig. 3b is a diagram illustrating an embodiment of computer systems configured to communicate using a communications network.

Fig. 4 is a flowchart illustrating an embodiment of a method for updating diagnostic files and information on a computer system.

Fig. 5 is an embodiment of types of information that may be included in a diagnostic information file.

Fig. 6a is a first part of an embodiment of a diagnostic script that may be used to determine what diagnostic routines a computer system supports.

Fig. 6b is a second part of an embodiment of a diagnostic script that may be used to determine what diagnostic routines a computer system supports.

Fig. 6c is a third part of an embodiment of a diagnostic script that may be used to determine what diagnostic routines a computer system supports.

Fig. 7a is an illustration of a first screen displayable by a display device in the embodiment shown in Fig. 1.

Fig. 7b is an illustration of a second screen displayable by a display device in the embodiment shown in Fig. 1.

Fig. 7c is an illustration of a third screen displayable by a display device in the embodiment shown in Fig. 1.

Detailed Description

5 Fig. 1 is a diagram illustrating an embodiment of a computer system. Fig. 1 depicts a computer system 100. Computer system 100 includes a processor 110, a chipset 120, a memory 130, and a plurality of devices 140a, 140b, and 140c. Device 140a may be coupled to a port 142a. Devices 140b and 140c may be coupled to a shared bus 142b. A portion of memory 130a within memory 130 may include a
10 diagnostic application 132, a diagnostic script 134, and a provided amount of diagnostic information 136. Diagnostic application 132 includes a plurality of diagnostic routines.

15 In computer system 100, diagnostic script 134 may be executed by computer system 100 and may identify a set of diagnostic routines within diagnostic application 132 that may be selected for execution by computer system 100. To do so, diagnostic script 134 may cause machine information corresponding to computer system 100 to be read. The machine information may include an operating system type and a machine type. The operating system type may be, for example, Windows 95™, Windows 98™, Windows NT™, Windows 2000™, Linux, or any other operating
20 system configured to run on computer system 100. The machine type may be an identifier that may be used to indicate the platform or system configuration of computer system 100 as specified by a manufacturer of computer system 100. The operating system type and machine type may be determined by accessing information stored in memory 130 and/or by using an application program interface (API)
25 provided by an operating system.

Once diagnostic script 134 has read the machine information, it may cause information corresponding to the machine information to be read from diagnostic information 136. Diagnostic information 136 may include information regarding components or diagnostic routines that are supported by one or more individual

systems offered by a computer manufacturer. This information may be broken down by operating system type and machine type such that diagnostic script 134 may be configured to detect a list of included components or diagnostic routines based on the operating system type and then detect a list of excluded components or diagnostic routines based on the machine type. Using information in diagnostic information 136, diagnostic script 134 may identify the diagnostic routines in diagnostic application 132 that are supported by computer system 100. Diagnostic script 134 may cause the supported diagnostic routines in diagnostic application 132 to become selectable for execution. Diagnostic script 134 may also cause the remaining, unsupported diagnostic routines in diagnostic application 132 to become not selectable for execution. The supported diagnostic routines may be selected for execution by any suitable means. For example, the supported diagnostic routines may be presented to a user in a user interface that displays an indicator for each supported diagnostic routine. A user may then select a supported diagnostic routine for execution using its indicator. The indicator may include a graphical and a textual representation of a component corresponding to the diagnostic routine. For example, if the component is a hard disk drive, the indicator may include a picture of a generic hard disk drive and the text "HARD DISK DRIVE". The supported diagnostic routines may also be selected for execution by a program configured to test one or more components in computer system 100. The program may receive an indication of the supported diagnostic routines and may use this indication to call one or more of the supported diagnostic routines. Once a supported diagnostic routine has been selected for execution, it may be executed by processor 110.

The supported diagnostic routines in a given computer system such as computer system 100 may each correspond to one or more components of the system. Components, as used herein, include all devices, ports, buses, and other elements of a computer system that may be operatively connected, by hardwired or wireless means, to the computer system. While examples of devices may include processors, memory devices such as a hard disk drive or SDRAM, graphics cards or accelerators, CD-ROM

or DVD drives, and input/output devices such as a keyboard, a mouse, or a joystick, the term components is intended to encompass all types of devices that may be included in or coupled to a computer system.

As shown in Fig. 1, computer system 100 includes device 140a coupled to
5 chipset 120 using port 142a. In addition, devices 140b and 140c are coupled to
chipset 120 using shared bus 142b. Chipset 120 is coupled to processor 110 and
memory 130. Diagnostic application 132 may include one or more diagnostic routines
for some or all of these components, i.e. devices 140a, 140b, and 140c, port 142a,
shared bus 142b, processor 110, chipset 120, and memory 130. For example, a
10 diagnostic routine included in diagnostic application 132 may be configured to test
memory 130. This diagnostic routine, along with other supported diagnostic
routines, may be detected by diagnostic script 134 and may become selectable for
execution.

It may be noted that diagnostic application 132, diagnostic script 134, and
15 diagnostic information 136 may be included in computer system 100 by a computer
manufacturer regardless of the platform or operating system of computer system 100.
Diagnostic script 134 may be configured to determine the platform and operating
system of computer system 100 and use that information along with information in
diagnostic information 136 to determine which of the diagnostic routines in
20 diagnostic application 132 may be selected for execution on computer system 100. A
computer manufacturer may include information regarding each platform and
operating system that it offers in diagnostic information 136. Accordingly, a
computer manufacturer may be able to install diagnostic application 132, diagnostic
script 134, and diagnostic information 136 in each system it sells with only relatively
25 minor modifications. In one embodiment configured to use a Windows operating
system, diagnostic information 136 may be included in a file using .INI format. In
another embodiment, diagnostic information 136 may be included in a file using XML
format. In other embodiments, diagnostic information 136 may be included in any

type of flat file accessible by diagnostic script 134. A specific embodiment of diagnostic information 136 is described below in Fig. 5.

Fig. 2a and Fig. 2b are a flowchart illustrating an embodiment of a method for indicating available diagnostic routines using system information in a computer system. Variations on the method are possible and contemplated. In Fig. 2a, a determination may be made as to whether a diagnostic application has been selected as indicated in step 202. The diagnostic application may be selected by a user or by a program seeking to cause one or more diagnostic routines to be executed. If a diagnostic application has not been selected, then the determination may be made again at a later time as indicated. If a diagnostic application has been selected, then a diagnostic script may be initiated as indicated in step 204. Machine information may be detected as indicated in step 206. In one embodiment, machine information may include an operating system type and a machine type as noted above. In other embodiments, machine information may include other types of information. Diagnostic information corresponding to the machine information may be detected as indicated in step 208. The diagnostic information may be contained in a file with a format such as .INI or XML as noted above. Certain diagnostic routines may be caused to become selectable for execution as indicated in step 210. An indicator may be displayed for each of the selectable diagnostic routines as indicated in step 212. In one embodiment, the indicator for each diagnostic routine may include a graphical and a textual representation of a component corresponding to the diagnostic routine.

Following point A in Fig. 2a to point A in Fig. 2b, a determination may be made as to whether a diagnostic routine indicator has been selected as indicated in step 214. In one embodiment, a diagnostic routine may be selected by a user. In another embodiment, a diagnostic routine may be selected by a program configured to test one or more components in a system. If a diagnostic routine indicator has been selected, then a diagnostic routine corresponding to the selected indicator may be executed as indicated in step 216. A determination may be made as to whether a diagnostic application exit has been selected as indicated in step 218. If a diagnostic

application exit has not been selected, then the determination of step 214 may be repeated as indicated. If a diagnostic application exit has been selected, then the diagnostic application may be exited as indicated in step 220.

Fig. 3a is a diagram illustrating an embodiment of computer systems configured to communicate using a communications network. Fig. 3a depicts a computer system 300 configured to communicate with a computer system 310 using a communications network 320. Computer system 300 may include a diagnostic application 302, a diagnostic script 304, and a provided amount of diagnostic information 306. Computer system 310 may include a diagnostic application 312, a diagnostic script 314, and a provided amount of diagnostic information 316.

Computer system 300 be a manufacturer's computer and computer system 310 may be a consumer's computer. Diagnostic application 312, diagnostic script 314, and diagnostic information 316 may be configured to operate similarly to diagnostic application 132, diagnostic script 134, and diagnostic information 136, respectively, as described above in Fig. 1. Diagnostic application 302, diagnostic script 304, and diagnostic information 306 may be the most recent versions of a diagnostic application, a diagnostic script, and a diagnostic information, respectively, used by a computer manufacturer.

At times, computer system 310 may be configured to determine whether diagnostic application 312, diagnostic script 314, and diagnostic information 316 have been updated, i.e. whether newer versions of each exist. Computer system 310 may be configured to compare the versions of diagnostic application 312, diagnostic script 314, and diagnostic information 316 with the versions of diagnostic application 302, diagnostic script 304, and diagnostic information 306, respectively, to make this determination. If computer system 310 does not have the newest versions of diagnostic application 312, diagnostic script 314, and / or diagnostic information 316, computer system 310 may be configured to download the newest version of one or more of diagnostic application 312, diagnostic script 314, and diagnostic information

316. Computer system 310 may be configured to do so automatically or at the request of its user.

Fig. 3b is a diagram illustrating an embodiment of computer systems configured to communicate using a communications network. Fig. 3b depicts computer system 300 configured to communicate with computer system 310 using communications network 320. Computer system 300 may include a diagnostic application 322, a diagnostic script 324, and a provided amount of diagnostic information 326.

Computer system 300 be a manufacturer's computer and computer system 310 may be a consumer's computer. Diagnostic application 322, diagnostic script 324, and diagnostic information 326 may be configured to operate similarly to diagnostic application 132, diagnostic script 134, and diagnostic information 136, respectively, as described above in Fig. 1. Diagnostic application 322, diagnostic script 324, and diagnostic information 326 may be the most recent versions of a diagnostic application, a diagnostic script, and a diagnostic information, respectively, used by a computer manufacturer.

Diagnostic application 322, diagnostic script 324, and diagnostic information 326 may be configured to operate on computer system 300 to identify diagnostic routines that may be executed using components in computer system 310. Diagnostic routines may be presented to a user of computer system 310 with a user interface. Computer systems 300 and 310 may be configured to communicate to allow diagnostic application 322 and diagnostic script 324 to be executed on computer system 300 to test components of computer system 310.

Figs. 3a and 3b illustrate the ability of a computer manufacturer to update a diagnostic application, diagnostic script, or diagnostic information using a communications network. As shown in Fig. 3a, updated versions may be downloaded to a user's system. In the system of Fig. 3b, updated versions are used automatically as the diagnostic application, the diagnostic script, and the diagnostic information are

all located on a manufacturer's computer and accessed from there each time they are used on a customer's computer.

Fig. 4 is a flowchart illustrating an embodiment of a method for updating diagnostic files and information on a computer system. In Fig. 4, a determination may be made as to whether a diagnostic application has been selected as indicated in step 402. If a diagnostic application has not been selected, then the determination may be made again at a later time as indicated. If a diagnostic application has been selected, then a determination may be made as to whether updated diagnostic information exists as indicated in step 404. If updated diagnostic information exists, then updated diagnostic information may be received as indicated in step 406. In step 408, a determination may be made as to whether an updated diagnostic script exists. If an updated diagnostic script exists, then the updated diagnostic script may be received as indicated in step 410. In step 412, a determination may be made as to whether an updated diagnostic routine exists. If an updated diagnostic routine exists, then the updated diagnostic routine may be received as indicated in step 414.

Fig. 5 is an embodiment of types of information that may be included in a diagnostic information file. Fig. 5 depicts a diagnostic information file 500. Diagnostic information file 500, entitled DIAGCONF.INI includes information corresponding to a plurality of operating system types 510, 512, 520, 522, 530, and 532, information corresponding to a component 540, 542, and 544, and information corresponding to a machine type 550, 552, 554, 556, 558, and 560. Fig. 5 depicts only a portion of the information that may be included in a diagnostic information file.

Operating system type information 510, 520, and 530 list the diagnostic routines for the components supported, separated by delimiters, for each corresponding operating system type 512, 522, and 532. For example, for the Win NT (Windows NT) operating system 522, the supported diagnostic routines include diagnostic routines for AGP, audio, AVI, and so on up to Zip Drive as shown in bracket 520. Similarly, the Win 9x (Windows 95 and 98) operating system 512 supports the diagnostic routines for the components listed in bracket 510 and the

Win 2k (Windows 2000) operating system 532 supports the diagnostic routines for the components listed in bracket 530. As may be seen, different operating systems may support different components. The diagnostic routines for the components supported by other operating systems may be listed in a similar manner.

5 Component information 540, 542, and 544 illustrate an example of information that may be used to display information corresponding to a component. In this example, the abstract "Hard Disk Drive Diagnostic" 542 and the icon file "HardDrive.jpg" 544 may be used as an indicator for systems that support a hard disk drive as indicated by text 540. Component information for other components
10 may be included in a similar manner.

15 Machine type information 550, 552, 554, 556, 558, and 560 illustrate an example of information that may be used list the diagnostic routines for the components that are not supported, separated by delimiters, for each operating system (bracket 554) for the machine ID byte 550. Comments 552 may be used to describe the machine type. List 556 lists the components whose diagnostic routines are not supported in the Windows 95 and 98 operating systems. Similarly, lists 558 and 560 list the components whose diagnostic routines are not supported in the Windows NT and Windows 2000 operating systems, respectively. The components whose diagnostic routines are not supported in other operating systems may be listed
20 similarly. As may be seen, different systems or platforms may support different components for each operating system. Machine type information may be included for each system or platform offered by a computer manufacturer.

25 A diagnostic script, such as diagnostic script 134 in Fig. 1, may use diagnostic information file 500 to identify diagnostic routines that may be selected for execution. For example, a diagnostic script for a computer system with machine ID byte 550 ("0xBA") running Windows NT may include the diagnostic routines for the components that are included in the bracketed list 520 and not excluded by the list 558. The script may use the component information for each of these components,

such as component information 540, 542, and 544 for the hard disk drive, to display the selectable diagnostics to a user.

Fig. 6a, Fig. 6b, and Fig. 6c is an embodiment of a diagnostic script 600 that may be used to determine what diagnostic routines a computer system supports. The diagnostic script 600 may be composed of Java Scripts / Methods / Functions as indicated in Figs. 6a, 6b, and 6c. The script may get a diagnostic information file location as highlighted by a comment 602. The script may then determine an operating system platform by calling a Java method which calls a Windows API that returns the operating system that is installed as highlighted by a comment 604. Next, the script may load a list of supported diagnostics for the operating system platform from the information file as highlighted by a comment 606. The script may then load a list of unsupported diagnostic routines from the information file based on machine and operating system platform as highlighted by a comment 608. The script may remove the excluded diagnostics from the supported list as highlighted by a comment 610 and may build a list of supported diagnostic and presentation items from the information file as highlighted by a comment 612. The script may next set the environment global space as highlighted by a comment 614. The script may load the machine ID for the machine under test as highlighted by a comment 616. The script may then call a Java method that extracts the machine ID from the SMBIOS table as highlighted by a comment 618. Finally, the script may create the list of supported diagnostics and their presentation items as highlighted by a comment 620.

Fig. 7a, Fig. 7b, and Fig. 7c are an illustration of a first screen, a second screen, and a third screen displayable by a display device in the embodiment shown in Fig. 1. When a user selects a help application, a user may be present with a screen 700. One option the user may have may be to launch a diagnostic application. In screen 700, the user may launch a diagnostic application by selecting the area indicated by an arrow 702. By selecting the area indicated by arrow 702, the user may also launch a diagnostic script that is configured to identify diagnostic routines that are selectable for execution.

The results provided by the diagnostic script may be used to create screen 710 shown in Fig. 7b. Screen 710 includes a list of components 712 supported by the system. When a component in list 712 is highlighted (such as by moving the mouse over the text of the component in list 712), an indicator corresponding to the component may be displayed as indicated by an indicator 714. Indicator 714 includes a graphical representation of the component and a textual representation of the component, in this case a hard disk drive. It may be noted that the graphical representation may correspond to an icon in the diagnostic information file, such as icon 544 in Fig. 5, and the textual representation may correspond to an abstract in the diagnostic information file, such as abstract 542 in Fig. 5.

A screen 720 may be displayed in response to indicator 714 being selected. As may be seen, screen 720 includes textual information regarding questions a user may have and diagnostic routines a user may cause to be executed. In screen 720, a user may cause diagnostic routines for the selected component to be executed by selecting an indicator 722.

As can be seen, the principal advantages of these embodiments may be that an entire suite of diagnostic routines may be installed on each computer system a computer manufacturer offers while only supported diagnostic routines may be made selectable for execution on a particular system based on certain characteristics of that system. In this way, the process of installing diagnostic routines may be substantially similar or even identical for each system that a computer manufacturer offers. In addition, these embodiments may advantageously allow a computer manufacturer to change the set of supported diagnostic routines on a system or systems while minimizing the development effort and test cycle for each change. In certain embodiments, the changes may be made by simply changing one or more delimited fields in a diagnostic information file. The embodiments may also advantageously allow a computer manufacturer to easily offer additional systems or test support with minimal development effort and testing. In certain embodiments, information corresponding to a new system may be added to a diagnostic information file such

that the information may be accessed by a diagnostic script to identify the diagnostic routines that are supported in the new system.

Although illustrative embodiments have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiment may be employed without a corresponding use of other features. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the embodiments disclosed herein.

Claims

What is claimed is:

1. A method comprising:
 - detecting machine information;
 - detecting diagnostic information corresponding to the machine information; and
 - causing one of a plurality of diagnostic routines to be selectable for execution according to the diagnostic information.
2. The method of claim 1, further comprising:
 - displaying an indicator corresponding to the one of the plurality of diagnostic routines.
3. The method of claim 2, wherein the indicator includes a graphical representation of a component corresponding to the one of the plurality of diagnostic routines and a textual representation of the component.
4. The method of claim 3, further comprising:
 - selecting the indicator; and
 - executing the one of the plurality of diagnostic routines in response to the selecting.
5. The method of claim 1, wherein the machine information includes an operating system type and a machine type, and wherein the diagnostic information includes a list of included components corresponding to the operating system type and a list of excluded components corresponding to the machine type.

6. The method of claim 5, wherein a component corresponding to the one of the plurality of diagnostic routines is included in the list of included components, and wherein the component is not included in the list of excluded components.

7. A computer system comprising:
a first computer including:
a processor; and
a memory coupled to the processor;
the memory including a diagnostic script, a plurality of diagnostic routines, first diagnostic information, and machine information; and
the diagnostic script being executable by the processor to cause the machine information to be read, to cause a portion of the first diagnostic information corresponding to the machine information to be read, and to cause one of the plurality of diagnostic routines to become selectable for execution by the processor according to the portion of the first diagnostic information.

8. The computer system of claim 7, wherein the diagnostic script is executable by the processor to cause an indicator corresponding to the one of the plurality of diagnostic routines to be displayed.

9. The computer system of claim 8, wherein the indicator includes a graphical representation of a component corresponding to the one of the plurality of diagnostic routines and a textual representation of the component.

10. The computer system of claim 9, wherein the processor is configured to execute the one of the plurality of diagnostic routines in response to the indicator being selected.

11. The computer system of claim 7, wherein the machine information includes an operating system type and a machine type, and wherein the first diagnostic information includes a list of included components corresponding to the operating system type and a list of excluded components corresponding to the machine type.

12. The computer system of claim 11, further comprising:
a component coupled to the processor;
wherein the component is included in the list of included components and not included in the list of excluded components, and wherein the component corresponds to the one of the plurality of diagnostic routines.

13. The computer system of claim 7, further comprising:
a second computer; and
a communications network;
the first computer and second computer being configured to communicate using the communications network; and
the first computer being configured to detect second diagnostic information on the second computer and to receive the second diagnostic information.

1 14. A computer program product comprising:

2 a computer program processable by a computer system for causing the
3 computer system to:

4 read machine information;

5 read diagnostic information corresponding to the machine
6 information; and

7 cause one of a plurality of diagnostic routines to become
8 selectable for execution according to the portion of the diagnostic
9 information; and

10 an apparatus from which the computer program is accessible by
11 the computer system.

1 15. The computer program product of claim 14, wherein the computer program is
2 processable by the computer system for causing an indicator corresponding to
3 the one of the plurality of diagnostic routines to be displayed.

1 16. The computer program product of claim 15, wherein the indicator includes a
2 graphical representation of a component corresponding to the one of the
3 plurality of diagnostic routines and a textual representation of the component.

1 17. The computer program product of claim 16, wherein the computer system is
2 configured to execute the one of the plurality of diagnostic routines in response
3 to the indicator being selected.

1 18. The computer program product of claim 14, wherein the machine information
2 includes an operating system type and a machine type, and wherein the
3 diagnostic information includes a list of included components corresponding to
4 the operating system type and a list of excluded components corresponding to
5 the machine type.

PATENT

Docket No.: DC-02404 (16356.543)


- 1 19. The computer program product of claim 18, wherein a component of the
2 computer system corresponding to the one of the plurality of diagnostic
3 routines is included in the list of included components, and wherein the
4 component is not included in the list of excluded components.

**A SYSTEM AND METHOD FOR IDENTIFYING EXECUTABLE
DIAGNOSTIC ROUTINES USING MACHINE INFORMATION
AND DIAGNOSTIC INFORMATION IN A COMPUTER SYSTEM**

Abstract of Disclosure

A system and method for identifying executable diagnostic routines using machine information and diagnostic information in a computer system is provided. The method includes detecting machine information, detecting diagnostic information corresponding to the machine information, and causing one of a plurality of diagnostic routines to be selectable for execution according to the diagnostic information.

a-101307v1






Fig. 2a

002020" 0342260




Fig. 2b




Fig. 3a




Fig. 3b







Fig. 4


DIAGCONF.INI File 500


0040200"03422960


[Win9x]  512

SupportedDiags=AGP|Audio|AVI|CD/DVD-ROM|CMOS|CPU|
Extended SMART Drive|Floppy Drive|Hard Drive|Infrared Port|Joystick|Keyboard|
Microphone|Modem|Monitor|Mouse|Network Adapter|Parallel Port|PCI|PCMCIA|
Printer|SCSI|Serial Port|SMART Drive|Super Disk|System Diagnosis|System Memory|
USB|Video Adapter|Zip Drive  510

[WinNT]  522


SupportedDiags=AGP|Audio|AVI|CD/DVD-ROM|CMOS|CPU|Extended SMART Drive|
Floppy Drive|Hard Drive|Joystick|Keyboard|Microphone|Modem|Monitor|Mouse|
Network Adapter|Parallel Port|Printer|SCSI|Serial Port|SMART Drive|Super Disk|
System Diagnosis|System Memory|Tape Backup|Video Adapter|Zip Drive  520


[Win2k]  532


SupportedDiags=AGP|Audio|AVI|CD/DVD-ROM|CMOS|CPU|Extended SMART Drive|
Floppy Drive|Hard Drive|Joystick|Keyboard|Microphone|Modem|Monitor|Mouse|
Network Adapter|Parallel Port|Printer|SCSI|Serial Port|SMART Drive|Super Disk|
System Diagnosis|System Memory|Tape Backup|Video Adapter|Zip Drive|USB  530

.

.

[Hard Drive]  540


abstract=HardDisk Drive Diagnostic  542

icon=HardDrive.jpg  544


.

.


.


[0xBA]  550



;Code=Mummy

;Audience=Dimension  552

;Computer=Dimension Columbus II

Win9xExclude=AVI|Extended SMART Drive|SMART Drive|Monitor|Infrared Port|
PCMCIA|Tape Backup  556

WinNTEExclude=AVI|Extended SMART Drive|SMART Drive|Monitor|Infrared Port|
PCMCIA|PCI|USB  558

Win2KExclude=AVI|Extended SMART Drive|SMART Drive|Monitor|Infrared Port|
PCMCIA|PCI  560  554

.

.

.

Fig. 5

Java Script/Methods/Functions: 600

```
function parseDiagIni (sMachined)
{
    // *** Get Diagnostic Information File location.
    var sIniFile = getDiagConfFile ();      ↖ 602

    // *** Determine OS platform, a Java method is called which in turn calls a
    // Windows API that returns the OS installed.                                ↖ 604
    var sOSString = "";
    if (IsWindowsNT ())
        sOSString = "WinNT";
    else if (IsWindows2000 ())
        sOSString = "Win2K";
    else if (IsWindows98 () || IsWindows95 ())
        sOSString = "Win9x";

    // *** Load list of supported diagnostics for the OS platform from the
    // information file.                                                         ↖ 606
    var xSupportedDiags = iniApi.GetEntry (sOSString, "SupportedDiags",
sIniFile);
    xSupportedDiags.Print ();
    if (xSupportedDiags.GetReturnCode () != 0) {
        DebugPrint ("No SupportedDiags variable for " + sOSString);
        return;
    }
    sSupportedDiags = xSupportedDiags.GetAttribute ("value");
    DebugPrint ("SupportedDiags = " + sSupportedDiags);
    var aSupportedDiags = parseLine (sSupportedDiags);
}
```

Fig. 6a

```

// *** Load list of unsupported diagnostics from the information file based
on machine and OS platform.
var xExcludeDiags = iniApi.GetEntry (sMachineId, sOSString + "Exclude",
sIniFile);
    xExcludeDiags.Print ();
if (xExcludeDiags.GetReturnCode () == 0) {
    DebugPrint("Now entering - excluded diags section - svk ");
    sExcludeDiags = xExcludeDiags.GetAttribute ("value");
    DebugPrint ("ExcludeDiags = " + sExcludeDiags);
    var aExcludeDiags = parseLine (sExcludeDiags);
    // *** Remove the excluded diagnostics from the supported list.
    for (var i = 0; i < aExcludeDiags.length; i++) {
        for (var j = 0; j < aSupportedDiags.length; j++) {
            if (aExcludeDiags[i] == aSupportedDiags[j]) {
                aSupportedDiags[j] = "";
            }
        }
    }
}
else {
    DebugPrint ("No Exclude list for " + sOSString + " on " + sMachineId);
}

```

Fig. 6b

// * Build list of supported diagnostic and presentation items from the information file.** 612

```
// Diagnostic|Abstract|Icon File Name||Diagnostic...
aDiagConfData = new Array ();
aDiagConfData[0] = "abstract";
aDiagConfData[1] = "icon";
var sFinalDiagsSupported = "";
var sSeparator = "|";
var sSuperSeparator = "||";
for (var j = 0; j < aSupportedDiags.length; j++) {
    DebugPrint ("Testing " + aSupportedDiags[j]);
    if ("" != aSupportedDiags[j]) {
        var Abstract = "";
        var Icon = "";
        var xDiagConfDataAbs = iniApi.GetEntry (aSupportedDiags[j],
aDiagConfData[0], sIniFile);
        if (xDiagConfDataAbs.GetReturnCode () == 0)
            Abstract = xDiagConfDataAbs.GetAttribute ("value");
        var xDiagConfDataIcon = iniApi.GetEntry (aSupportedDiags[j],
aDiagConfData[1], sIniFile);
        if (xDiagConfDataIcon.GetReturnCode () == 0)
            Icon = xDiagConfDataIcon.GetAttribute ("value");
        sFinalDiagsSupported = sFinalDiagsSupported + aSupportedDiags[j] +
sSeparator + Abstract + sSeparator + Icon + sSuperSeparator;
    }
}
// *** Set the environment global space 614
iapi.SetGlobalArg ("DellSupportedDiags", sFinalDiagsSupported);
}
```

// * Load the machine id for the machine under test.**

```
s = new java.lang.StringBuffer (200); 616
```

// * Call a Java method that extracts the Machine ID from the SMBIOS table** 618

```
DellAPI.GetMachineID (s);
if (s.toString ().length () > 0) {
    // Set the Machine Id in the following format: 0xFF. This is used to look the
    system up in DiagConf.ini
    g_sMachineId = "0x" + s.toString ();
}
```

// * Create the list of supported diagnostics and their presentation items.**


```
parseDiagIni (g_sMachineId); 620
```

Fig. 6c

The image is a screenshot of a web browser window displaying the Dell Resolution Assistant. The browser's title bar reads "Dell Resolution Assistant - Microsoft Internet Explorer". The address bar shows the URL "http://localhost:5197/Dell/mots/content/template/ResolutionAssistant mots?vendorId=Dell". The page features a navigation bar with icons for Back, Forward, Stop, Refresh, Home, Search, Favorites, History, Mail, Print, Edit, and Discuss. The main content area is titled "DELL RESOLUTION ASSISTANT" and includes a "DIMENSION™" logo and a "support DIRECT FROM DELL™" logo. A large image of a Dell computer system (monitor, tower, keyboard, mouse, and speakers) is centered on the page. To the left of the computer, a text block welcomes users and provides instructions on how to use the tool. Below the computer image, there is a "Service Tag: CMSB4" and a "702" with an arrow pointing to a button labeled "Diagnose the problem for me...". Other buttons include "Common solutions for my problem..." and "Connect to a Dell Support Technician...". The footer contains links for Home, Support, Service Status, Preferences, Privacy Policy, and About. The browser's status bar at the bottom indicates "Local intranet".

Fig. 7a

002020-0346250



710 →

Fig. 7b

Dell Resolution Assistant - Microsoft Internet Explorer

File Edit View Favorites Tools Help


Back Forward Stop Refresh Home Search Favorites History Mail Print Edit Discuss

Address http://localhost:5197/Dell/mots/content/template/ResolutionAssistant.mots?vendorId=Dell

Go Links

DELL RESOLUTION ASSISTANT

DIMENSION™



DIRECT FROM DELL™

HardDisk Drive Diagnostic

FAQ's *Read a Frequently Asked Question about the device or problem.*

- [What size hard drive can I add to my Dell Dimension System?](#)
- [Why is my hard drive so noisy?](#)
- [How do I add a hard drive to my system?](#)

[More FAQ's](#)

 In order to be assisted by Online-service, you must first run this diagnostic which will gather all the relevant information that is required by the online technician to process your request.

OVERVIEW *Run a diagnostic test on the device.*


This diagnostic consists of four subtests.

- Linear Seek Test — Verifies correct operation of the drive heads
- Random Seek Test — Verifies correct operation of the drive heads
- Funnel Seek Test — Verifies correct operation of the drive heads
- Surface Scan Test — Scans the drive for defective sectors

This diagnostic tests the hard-disk drive controller, the drive mechanism, and the disk surface itself. All installed fixed disks are tested.

NOTE: Running a diagnostic test allows Dell to access information on your computer. If you do not want Dell to access this information, change the Resolution Assistant security settings found under preferences in the bottom navigation bar of this interface.

[Click here to run the diagnostic test.](#)



Go back to the [List of Diagnostics](#).

722

Copyright © 1999-2000 Dell Inc. All Rights Reserved

Home | Support | Service Status | Preferences | Privacy Policy | About

Local intranet


720 

Fig. 7c

**DECLARATION AND POWER OF ATTORNEY FOR
PATENT APPLICATION**

As below named inventors, we hereby declare that:

Our residence, post office address and citizenship are as stated below next to our names;

We believe we are the original, first and joint inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled

**A SYSTEM AND METHOD FOR IDENTIFYING EXECUTABLE
DIAGNOSTIC ROUTINES USING MACHINE INFORMATION
AND DIAGNOSTIC INFORMATION IN A COMPUTER SYSTEM**

the specification of which: (check one)

XXX is attached hereto.

_____ was filed on _____
under Attorney's Docket Number _____
as Application Serial No. _____
and was amended on _____ (if applicable).

We hereby state that we have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

We acknowledge the duty to disclose information which is material to the patentability of this application in accordance with 37 CFR 1.56.

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 USC 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

00000000-00000000

PATENT
DOCKET NUMBER: DC-02404 (16356.543)

POWER OF ATTORNEY: As a named inventor, we hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Jeffrey M. Becker	Reg. No. 35,442	Warren B. Kice	Reg. No. 22,732
James R. Bell	Reg. No. 26,528	Michael J. Balconi-Lamica	Reg. No. 34,291
Michael S. Bush	Reg. No. 31,745	Todd Mattingly	Reg. No. 40,298
Randall E. Colson	Reg. No. 40,566	David L. McCombs	Reg. No. 32,271
Michael A. Davis, Jr.	Reg. No. 35,488	David M. O'Dell	Reg. No. 42,044
Ruben DeLeon	Reg. No. 37,812	Anthony Peterman	Reg. No. 38,270
Henry Garrana	Reg. No. 27,887	Phillip B. Philbin	Reg. No. 35,979
Timothy Headley	Reg. No. 31,765	Diana L. Roberts	Reg. No. 36,654
Rita M. Irani	Reg. No. 31,028	Brandi W. Sarfatis	Reg. No. 37,713
Mark P. Kahler	Reg. No. 29,178	David Simmons	Reg. No. 43,124

Send correspondence to David L. McCombs, Haynes and Boone, L.L.P., 901 Main Street, Suite 3100, Dallas, Texas 75202-3789 and direct all telephone calls to David L. McCombs at 214/651-5533.

=====

FULL NAME OF INVENTOR: Michael A. Brundridge

INVENTOR'S SIGNATURE: Michael A. Brundridge DATED: August 04, 2000

RESIDENCE: 428 Doe Run, Georgetown, Texas 78628

CITIZENSHIP: United States of America

POST OFFICE ADDRESS: 428 Doe Run, Georgetown, Texas 78628

=====

FULL NAME OF INVENTOR: Javier L. Jimenez

INVENTOR'S SIGNATURE: Javier L. Jimenez DATED: August 04, 2000

RESIDENCE: 8926 Joachim Lane, Austin, Texas 78717

CITIZENSHIP: United States of America

POST OFFICE ADDRESS: 8926 Joachim Lane, Austin, Texas 78717